

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/AU05/000297

International filing date: 02 March 2005 (02.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: AU
Number: 2004901692
Filing date: 29 March 2004 (29.03.2004)

Date of receipt at the International Bureau: 22 March 2005 (22.03.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT/AU2005/000297

Australian Government


Patent Office
Canberra

I, LEANNE MYNOTT, MANAGER EXAMINATION SUPPORT AND SALES hereby certify that annexed is a true copy of the Provisional specification in connection with Application No. 2004901692 for a patent by HYATT NICHOLAS HADDAD as filed on 29 March 2004.

WITNESS my hand this
Fourteenth day of March 2005

A handwritten signature in dark ink, appearing to be 'LM' or 'Leanne Mynott'.

LEANNE MYNOTT
MANAGER EXAMINATION SUPPORT
AND SALES



Hyatt Nicholas Haddad

A U S T R A L I A

Patents Act 1990

PROVISIONAL SPECIFICATION

for the invention entitled:

"A Case for a Cigarette Packet"

The invention is described in the following statement:

A CASE FOR A CIGARETTE PACKET

5

Technical Field of the Invention

The present invention relates to a case for a cigarette packet.

10

Background of the Invention

Cigarette packets bear trade marks and other indicia that help to distinguish the cigarettes of one manufacturer from those of another. Manufacturers of cigarettes typically manufacture a range of cigarettes that are each distinguished from one another by their respective colours and/or designs. While, such markings and colours assist in product selection, consumers may not wish to themselves advertise their preferred brand and style of cigarettes after the product has been purchased. In addition, may not necessarily find that their preferred cigarette packet has aesthetic value.

20

Cigarette packets in Australia, for example, bear government health warnings that are designed to confront smokers with the dangers of smoking. While the government health warnings may be useful in informing smokers of these dangers, they are laid bare for all to see and may be offensive to some people.

25

An object of preferred embodiments of the present invention is to overcome or ameliorate one or more of the above mentioned difficulties, or at least provide a useful alternative.

Summary of the Invention

30

In accordance with one aspect of the present invention, there is provided a case for a cigarette packet including a lid and a hollow receptacle that is closed at one end, a first portion of the lid being shaped to receive and seat therein a lid portion of the cigarette packet and the receptacle being shaped to receive and seat therein a body portion of the cigarette packet.

35

- 2 -

In accordance with another aspect of the present invention, there is provided a case for a cigarette packet including a lid and a hollow receptacle that is closed at one end, the receptacle being shaped to receive and seat therein a body portion of the cigarette packet
5 and the lid being arrangable to extend over and cover an open end of the receptacle so as to secure a cigarette packet stored therein.

Preferably, the case includes a wallet that is coupleable to a side of the case.

10 Brief Description of the Drawings

Preferred embodiments of the present invention are hereafter described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

- 15 Figure 1 is a diagrammatic illustration of an isometric view of a front aspect of a case for a cigarette packet in accordance with a preferred embodiment of the present invention;
Figure 2 is a diagrammatic illustration of a rear aspect of the case shown in Figure 1;
Figure 3 is a diagrammatic illustration of an isometric view of a front aspect of a lid of the case shown in Figures 1 and 2;
- 20 Figure 4 is a diagrammatic illustration of a side aspect of the of the lid of the case shown in Figure 3;
Figure 5 is a diagrammatic illustration of an isometric view of a rear aspect of the lid of the case shown in Figures 3 and 4;
Figure 6 is a diagrammatic illustration of an isometric view of a front aspect of a receptacle
25 of the case shown in Figures 1 and 2;
Figure 7 is a diagrammatic illustration of an isometric view of a front aspect of a cigarette packet;
- 30 Figure 8 is a diagrammatic illustration of an isometric view of a front aspect of the receptacle shown in Figures 6 with the cigarette packet shown in Figure 7 seated therein;
Figure 9 is a diagrammatic illustration of a side aspect of the lid of the case shown in Figures 3 and 4 coupled to the cigarette packet shown in Figure 7;

Figure 10 is a diagrammatic illustration of an isometric view of a rear aspect of the lid coupled to the cigarette packet shown in Figure 9;

Figure 11 is a diagrammatic illustration of an isometric view of a front aspect of the lid and coupled to the cigarette packet shown in Figures 9 and 10;

5 Figure 12 is a diagrammatic illustration of a partially exploded isometric view of a front aspect of the case shown in Figure 1 coupled to the cigarette packet shown in Figure 7;

Figure 13 is a diagrammatic illustration of an isometric view of a front aspect of the case shown in Figure 1 coupled to the cigarette packet shown in Figure 7;

10 Figure 14 is a diagrammatic illustration of an isometric view of a front aspect of a case in accordance with a preferred embodiment of the invention;

Figure 15 is a diagrammatic illustration of an isometric view of a rear aspect of a case in accordance with a preferred embodiment of the invention;

Figure 16 is a diagrammatic illustration of an isometric view of a further rear aspect of the case shown in Figure 15;

15 Figure 17 is a diagrammatic illustration of an isometric view of a front aspect of the wallet shown in Figure 16 arranged in a first position;

Figure 18 is a diagrammatic illustration of an isometric view of a front aspect of the wallet shown in Figure 17 arranged in a second position;

20 Figure 19 is a diagrammatic illustration of an isometric view of a front aspect of a case for a cigarette packet in accordance with a preferred embodiment of the present invention;

Figure 20 is a diagrammatic illustration of an isometric view of a front aspect of the case shown in Figure 19;

Figure 21 is a diagrammatic illustration of an isometric view of a front aspect of a case in accordance with a preferred embodiment of the invention; and

25 Figure 22 is a diagrammatic illustration of an isometric view of a front aspect of the case shown in Figure 19.

Detailed description of Preferred Embodiments of the Invention

The case 10 shown in Figures 1 and 2 is a decorative and protective covering for a cigarette packet (not shown). The case 10 includes a hollow receptacle 12 that is closed at one end. The receptacle 12 is shaped to receive, and store therein, a cigarette packet. The case 10 also includes a lid 14 that is positionable over an open end of the receptacle 12 to thereby secure the contents of the receptacle 12 therein.

The lid 14 includes first and sections 16,18, as shown in Figures 3 to 5. The first section 16 is rectangular in shape and has a height, h_f , and a length, l_f , that each approximate the height and the length of a cigarette packet respectively. The width, w_f , of the first section 16 is, for example, 2mm.

The second section 18 is formed in the shape of a box having one open side. The length, l_s , of the second section 18 is equal to the length, l_f , of the first section 16. The width, w_s , of the second section 18 approximates the width of the cigarette packet. The height, h_s , of the second section 18 approximates the height of a lid portion of the cigarette packet. The second section 18 is shaped to receive the lid portion of the cigarette packet through the above-mentioned open side.

The first section 16 is arranged with respect to the second section 18 such that a length, l_s , of the second section 18 is parallel to and abutting a length, l_f , of the first section 16. Further, the abutting lengths of the first and second sections 16,18 are coupled together by a hinge 20. The mentioned abutting length of the second section 18 is a length of the second section 18 that, in part, defines the open side of the box-shaped second section 18.

The open end 22 of the receptacle 12 shown in Figure 6 is shaped to receive an end portion 24 of the cigarette packet 26 shown in Figure 7. The length, l_r , and width, w_r , of the receptacle 12 are slightly greater than the length, l_c , and the width, w_c , of the cigarette packet, such that the packet 26 can pass through the open end 22 of the receptacle 12. The packet 26 is seated within the receptacle 12 when the end portion 24 of the packet 26 abuts

- 5 -

the closed end of the receptacle 12. The height, h_r , of the receptacle 12 is approximates the height, h_c , of a body portion 28 of the cigarette packet 26. When the packet is seated in the receptacle 12 in the described manner a lid portion 30 of the cigarette packet 26 protrudes from the receptacle 12 in the manner shown in Figure 8.

5

The open side of the box-shaped second section 18 of the lid 14 is shaped to receive the lid portion 30 of the cigarette packet 26 in the manner shown in Figures 9 to 11. The length, l_s , and the width, w_s , of the second section 18 of the lid 14 are such that the lid 30 of the cigarette packet 26 (having length, l_c , and width, w_c) can pass through the open side of the
10 box-shaped second section 18 of the lid 14. The lid 30 of the packet 26 is seated within the second section 18 when an end portion of the lid 30 of the cigarette packet 26 abuts the closed end of the second section 18. The height, h_s , of the second section 18 of the lid 14 approximates the height of the lid 30 of the cigarette packet 26. When the lid 30 of the cigarette packet 26 is seated in the second section 30 of the lid 14 in the described manner,
15 a body portion 28 of the cigarette packet 26 protrudes from the second section 18 of the lid 14 in the manner shown in Figures 9 to 11.

The case 10 is fitted to the cigarette packet 26 by first seating the lid 30 of the cigarette packet 26 within the second section 18 of the lid 14 and then seating the body portion of
20 the cigarette packet, together with the first section 16 of the lid 14 within the receptacle 12, as shown in Figure 12 and Figure 13. Alternatively, the cigarette packet 26 may first be seated in the receptacle 12 and then fitted to the lid 14 in the described manner.

In one example of the invention, the lid 14 is made of a silicon rubber material and
25 resiliently engages the lid 30 of the cigarette packet 26 when fitted in the above-described manner. Alternatively, the lid 30 of the cigarette packet 26 may be coupled to the second section 18 of the lid 14 in any suitable manner.

The hinge 20 is preferably a fold or a crease in the silicon rubber material of the lid 14.
30 The hinge 20 thereby allows the second section 18 of the lid 14 to rotate about the first section 16 of the lid 14. Alternatively, the hinge may be formed of any suitable material

- 6 -

that is coupled to both the first and second sections 16,18 of the lid 14.

The case 10 shown in Figure 14 includes a pocket 32 of suitable size to support a cigarette lighter. The pocket is located on the periphery of the case 10 and is made of a fabric material. Alternatively, the pocket may be made of any suitable material.

The case 10 shown in Figures 15 and 16 includes a wallet 34. The wallet 34 is coupleable to a rear side of the case 10. The wallet 34 is secured to the case 10 by way of a zipper (not shown). The zipper extends around the periphery of one side of the wallet 34. The rear side of the case 10 includes corresponding portions of the zipper and the wallet is thereby securable to the case 10. The wallet may alternatively be secured to the case 10 by corresponding male and female velcro strips secured to respective opposed sides of the wallet 34 and the case 10. The wallet 34 may otherwise be secured to the case 10 by any suitable means. The wallet 34 shown in figures 17 and 18 includes pockets 36 for storing cards, money and other associated items.

The case 50 shown in Figures 19 and 20 includes a hollow receptacle 52 that is closed at one end. The receptacle 52 is shaped to receive, and store therein, a cigarette packet 26. The case 50 also includes a lid 54 that is positionable over the open end of the receptacle 52 to thereby secure the contents of the receptacle 52 therein. The case functions in an analogous manner to the above-described case 10. The case 50 also includes a capping 56 that can be fitted over the lid 54. An outer peripheral portion 58 of the lid 54 includes a plurality of raised rubber portions 60 that are positioned to resiliently engage the capping 56 when fitted over the lid 54 in the described manner. The raised rubber portions 60 bear against the capping 56 when so fitted and thereby secure the capping 56 to the lid 54.

The capping 56 is preferably stainless steel. However, any suitable material may be used. The capping 56 increases the aesthetic value of the case 50 as well as further protecting the cigarette packet stored therein.

30

- 7 -

The case 62 shown in Figure 21 functions as a decorative and protective covering for a cigarette packet (not shown). The case 62 includes a hollow receptacle 64 that is closed at one end. The receptacle 64 is shaped to receive, and store therein, a cigarette packet. The case 62 also includes a lid 66 that is positionable over an open end of the receptacle 64 to
5 secure the contents of the receptacle 64 therein. The lid 66 is formed of a fabric material and is secured to the receptacle 64 by a hinge 68.

The open end of the receptacle 64 is shaped to receive an end portion 24 of the cigarette packet 26 shown in Figure 7. The length and width of the receptacle 64 is slightly greater
10 than the length and the width of the packet of cigarettes, so that the cigarette packet 26 can pass through the open end of the receptacle 64. The packet 26 is seated within the receptacle 64 when the end portion 24 of the cigarette packet 26 abuts the closed end of the receptacle 64. The height of the receptacle 64 is equivalent to the height of a body portion
15 28 of the cigarette packet 26. When the packet is seated in the receptacle 64 in the described manner, an open end of the packet 26 is coplanar with the open end of the receptacle 64.

The lid 66 extends from the hinge 68, over the open end of the receptacle 64, to a position overlying the front side of the case 62 in the manner shown in Figure 22. The lid 66 is
20 coupleable to the front side of the case by way of corresponding male and female velcro strips secured to respective opposed portions of the front side of the case 62 and to the lid 68. Alternatively, the lid may be secured to the case by any suitable means.

The case 62 is fitted to the cigarette packet 26 by first seating the body portion 28 of the cigarette packet 26 within the receptacle 64 in the above described manner. The cigarette
25 packet 26 is secured in that position by coupling the lid 66 to the receptacle 64 in the described manner.

The case 62 is suitable for use with soft cased cigarette packets that do not have a lid 30.
30 The case 62 also includes a pocket 70 of suitable size to support a cigarette lighter. The pocket is located on the periphery of the case 62 and is made of a fabric material.

- 8 -

Alternatively, the pocket 70 may be made of any suitable material.

The case 10,50,62 is formed of a fabric material. The fabric material may be, for example, a woven fabric material, leather, fake animal fur, etc.

5

The Claims Defining the Invention are as Follows:-

1. A case for a cigarette packet including a lid and a hollow receptacle that is closed at one end, a first portion of the lid being shaped to receive and seat therein a lid
5 portion of the cigarette packet and the receptacle being shaped to receive and seat therein a body portion of the cigarette packet.
2. The case claimed in claim 1, wherein a second portion of the lid is shaped for insertion into the receptacle to thereby couple the lid to the receptacle.
- 10 3. The case claimed in claim 2, wherein said first portion of the lid is coupled to the second portion of the lid by a hinge.
4. The case claimed in any one of claims 1 to 3, wherein the first portion of the lid
15 resiliently engages the lid of the cigarette packet when the lid of the cigarette packet is seated therein.
5. The case claimed in claim 4, wherein the lid is made of a silicon rubber material.
- 20 6. The case claimed in any one of the preceding claims, including a cap shaped to receive and secure therein the first portion of the lid.
7. The case claimed in claim 6, wherein the cap is made of stainless steel.
- 25 8. A case for a cigarette packet including a lid and a hollow receptacle that is closed at one end, the receptacle being shaped to receive and seat therein a body portion of the cigarette packet and the lid being arrangible to extend over and cover an open end of the receptacle so as to secure a cigarette packet stored therein.
- 30 9. The case claimed in any one of the preceding claims, including a wallet that is coupleable to a side of the case.

- 10 -

10. The case claimed in claim 9, wherein the wallet is coupleable to the case by way of a zipper having a first part secured to the wallet and a second part secured to said side of the case.
- 5
11. The case claimed in claim 9 or claim 10, wherein the wallet includes a plurality of pockets, the pockets being shaped to receive money or cards.
- 10 12. The case claimed in any one of the preceding claims, including a pocket coupled to a side of the case, the pocket being suitable for storing a cigarette lighter.

15 DATED this 29th Day of March, 2004

Hyatt Nicholas Haddad

by its Patent Attorneys

DAVIES COLLISON CAVE

20

1/21




Figure 1

2/21




Figure 2

3/21




Figure 3

4/21




Figure 4

5/21




Figure 5

6/21




Figure 6

7/21




Figure 7

8/21




Figure 8

9/21




Figure 9

10/21




Figure 10

11/21




Figure 11

12/21




Figure 12

13/21




Figure 13

14/21




Figure 14

15/21




Figure 15

16/21




Figure 16

17/21




Figure 17




Figure 18




Figure 19



Figure 20

20/21




Figure 21

21/21




Figure 22